



Green Mountain

BOILERS

- Available in 9 sizes from 45 to 295 Mbh.
- Dependable Cast Iron Heat Exchanger with Cast Iron Push Nipples. The Sections and Push Nipples expand at the same rate when heated. By using similar materials instead of less expensive gaskets the boiler maintains a water tight seal over time.
- An integrated Hi-Limit Control, Vent Damper Control and Intermittent Spark Control housed under a protective cover. Utilizes thermal purge logic to maximize fuel savings.
- Easy Installation and Maintenance – A compact design, low profile draft hood and top supply piping connections allow for easier installation. The pilot is mounted to the front of the burner base.
- 20 year prorated limited warranty

GMGW SERIES






Gas Fired Water Boiler

82% AFUE Gas Fired Water Boiler



**As rugged as the outdoors...
for dependable comfort every day.**

Green Mountain GMGW Series Gas Fired Hot Water Boiler

Dimensional Diagram	Model	Input Rate (Mbh) ⁽¹⁾	Heating Capacity (Mbh) ⁽¹⁾	Net AHRI Rating, Water (Mbh) ⁽²⁾	Air Cushion Tank ⁽³⁾	No. of Burners	AFUE %	
 <p style="text-align: center;">FRONT</p>	GMGWB045FE	45	37	32	15	1	82.0%	
	GMGWB070FE	70	57	50	15	2	82.0%	
	GMGWB096FE	96	79	69	30	2	82.0%	
	GMGWB120FE	120	98	85	30	3	82.0%	
	GMGWB145FE	145	119	103	30	3	82.0%	
	GMGWB170FE	170	140	122	30	4	82.0%	
	GMGWB195FE	195	160	139	30	4	82.0%	
	GMGWB245FE	245	201	174	30	5	82.0%	
	GMGWB295FE	295	242	210	60	6	82.0%	
<p>(1) Input rating for sea level to 2,000 ft. (610m) above sea level. United States, over 2000 ft (610m) above sea level. Reduce input rate 4% for every 1000 ft (304m) above sea level.</p> <p>(2) Net AHRI Water Ratings shown based on piping and pickup allowance of 1.15. Consult manufacturer before selecting boiler for installations having unusual piping and pickup requirements, such as intermittent system operation, extensive piping systems, etc.</p> <p>For forced hot water systems where boiler and all piping within area to be heated, boiler may be selected on basis of its heating capacity.</p> <p>(3) Recommended tank sizes for non-ferrous baseboard or radiant panel systems. Increase size for cast iron baseboard and radiation.</p>								
General Information (See Installation, Operation and Maintenance Manual for complete instructions)								
<p>Clearances (4) Required distances measured from boiler.</p> <p>*Definition of Alcove is three sided space with no wall in front of boiler. ANSI standard for alcove is 18 inches from appliance to leading edge of side walls as shown in IOM.</p>			Combustible Materials (Required) ⁽⁴⁾					
	Top	18" (457 mm)						
	Left Side (Control Side)	9" (229 mm)						
	Right Side	3" (76 mm)						
	Front	Alcove*						
	Back	8" (229 mm)						
Flue Connector	6" (152 mm)							
Connections (All Models)	Return/Supply Water 1-1/4", Gas In 1/2" NPT GMGWB045FE - GMGWB195FE, 3/4" NPT GMGWB245FE and GMGWB295FE, Propane Gas Inlet (All units) 1/2"							
Electrical	120 Volts AC, 60 hertz, 1 phase, Less than 12 amps (15 amp circuit recommended)							
Water Content	GMGWB045FE - 2.4 gals., GMGWB070FE & GMGWB096FE - 4.0 gals., GMGWB120FE & GMGWB145FE - 5.6 gals., GMGWB170FE & GMGWB195FE - 7.2 gals., GMGWB245FE - 8.8 gals., GMGWB295FE - 10.4 gals.							
Dimensions/Weights	Model	A	B	C	D	E	F	Weight
	GMGWB045FE	11-1/4"	5-5/8"	4"	27-1/8"	20-7/16"	4-15/16"	255 lbs.
	GMGWB070FE	15-1/8"	7"	5"	28-1/8"	20-15/16"	4-15/16"	305 lbs.
	GMGWB096FE	15-1/8"	7"	5"	28-1/8"	20-15/16"	4-15/16"	310 lbs.
	GMGWB120FE	19"	9-1/2"	6"	29-1/8"	21-7/16"	5-7/16"	355 lbs.
	GMGWB145FE	19"	9-1/2"	6"	29-1/8"	21-7/16"	5-7/16"	360 lbs.
	GMGWB170FE	22-7/8"	11-3/16"	7"	30-1/8"	21-15/16"	5-15/16"	420 lbs.
	GMGWB195FE	22-7/8"	11-3/16"	7"	30-1/8"	21-15/16"	5-15/16"	425 lbs.
	GMGWB245FE	26-3/4"	13-6/16"	8"	31-1/8"	22-7/16"	6-15/16"	495 lbs.
	GMGWB295FE	30-5/8"	15-5/16"	9"	32-1/8"	22-15/16"	8-15/16"	555 lbs.
Standard Equipment	<p>Boiler Control Module: High Limit Control</p> <p>Heat Exchanger: Cast Iron Heat Exchanger with Cast Iron Push Nipples.</p> <p>Combustion: Intermittent Electric Ignition Pilot System, Main Gas Burners, Combination Gas Control (Includes Automatic Gas Valve, Gas Pressure Regulator, Intermittent Pilot, Safety Shutoff, Pilot Flow Adjustment, Pilot Filter)</p> <p>Safety: Non-linting Safety Pilot, Spill Switch, Rollout Switch</p> <p>Other: Boiler Jacket, Circulator, Wiring Harness, Automatic Vent Damper, Vent Damper Relay, A.S.M.E. Relief Valve, Drain Valve.</p>							
	Options	Available in both natural gas or propane models.						
Certifications	<div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>C.S.A. Certified For Natural Gas Or Propane</p> </div> <div style="text-align: center;">  <p>US</p> </div> <div style="text-align: center;">  <p>Tested For 100 psi. ASME Working Pressure</p> </div> <div style="text-align: center;">  <p>AHRI CERTIFIED www.ahridirectory.org</p> </div> </div>							

All ratings and specifications subject to change.

PN 240009822 Rev. 10/13

